

GROWER®



Reliable agricultural machinery

Catalog | Range 55–80 HP

GT 554 GT 604 GT 704 GT 804

Equipment features, images, and specifications are subject to change without notice by **GROWER®*

GROWER®



Range 55 - 80 HP

GT 554 GT 604 GT 704 GT 804



Equipment features, images, and specifications are subject to change without notice by **GROWER®*

Technical Info

Transmission	GT 554	GT 604	GT 704	GT 804
Drive type	4WD / 4x4			
Gearbox gears number	8 + 2	F12+R12		
Max. forward speed (km/h) / (mph)	27.2 / 16.9	32,06 / 19,92	31.44 / 19.35	30,96 / 19,24
Engine				
Engine brand	GROWER			
Engine model	GE-LD554	GT-4C6-60U32	GT-4D32ZT31/704	GT-4C6-80U32
Engine type	Inline, 4-stroke, water-cooled, direct injection, turbocharged, intercooled, 4 cylinders			
Engine Rated power (kW) / (hp)	40.5 / 54.3	44,1 / 59,14	51.5 / 69.06	59 / 79.12
Engine Rated speed (rpm)	2400			
Engine Displacement (L) / (cc)	3.3 / 3300	3.26 / 3260	3.567 / 3567	3.47 / 3470
Cylinder Bore (mm) / (in)	94 / 3.70	95 / 3.74	104 / 4.09	98 / 3.85
Piston Stroke (mm) / (in)	105 / 4.13	115 / 4.52	105 / 4.13	115 / 4.52
Fuel tank capacity (L) / (gal)	55 / 14.5	90 / 23,78	90 / 23,78	90 / 23,78
Traction & Force				
Max. traction force (kN / Lbf)	18,85 / 4237,65	18,85 / 4237,65		19.992 / 4494.38
Max. lifting force (kg / lb)	725 / 1600	9,92 / 2230,1	12.36 / 2779.76	14.16 / 3183.29
PTO (Power Take - Off)				
PTO power (kW / hp)	34.38 / 46.1	37,5 / 50,29	43.8 / 58.74	50.15 / 67.25
PTO type	Rear-mounted, independent			
PTO speed (rpm)	540/760 or 540/1000			
PTO shaft size	8 splines, 6-spline optional			
Hydraulic System				
Number of hydraulic outlets	Two pairs			
Draft control	Height control and float control			
Dimensions & Weights				
Dimensions L xW xH (height to top of safety frame) (mm) / (in)	3790 × 1620 × 2130 / 149 × 63 × 83	3925×1728×2870 / 154x68x113		4530 × 2050 × 2930 / 178 × 80 × 115
Wheelbase (mm) / (in)	2035 / 80	2010 / 79		2030 / 80
Front track (mm) / (in)	1265 / 50			
Rear track width (mm) / (in)	1300 – 1500 / 49 – 59	1220, 1320, 1420, 1520 / 48, 52, 56, 60		1350, 1450, 1550 / 53, 57, 61
Min. ground clearance (mm) / (in)	354 / 13.9	360 / 14		370 / 15
Minimum operating weight with cab (kg) / (lb)	2120 / 4673	2565 / 5655		2720 / 5997
Steering & Hitch				
Steering type	Full hydraulic steering			Full hydraulic steering on front wheels
Hitch type / category	Rear-mounted three-point hitch, Category I and II			
Tires				
Front tire specification	7.50-16	8.3-24		
Rear tire specification	11.2-28	11-32		
Optional Configuration				
Front ballast (kg) / (lb)	Max. 112 / 246.92 (optional)			
Rear ballast (kg) / (lb)	Max. 200 / 440.92 (optional)			

GT 554 / GT 604 / GT 704 – Cab with A/C, 3 pairs of hydraulic outlets, front & rear iron ballast (1480 kg), optional tires 12.4×20 / 16.9×28 – 9.5×24 / 16.9×28 SET

GT 804 – Cab with A/C, 3 pairs of hydraulic outlets, front & rear iron ballast (1480 kg), optional tires 12.4×24 / 18.4×30

Equipment features and specifications may change without notice from **GROWER.*

GROWER®



Legal Notice:

The information contained in this catalog, including but not limited to technical specifications, descriptions, configurations, illustrations, images, performance data, capacities, and any other information, is provided for informational and reference purposes only. Such information may be modified, updated, or corrected at any time without prior notice.

GROWER® assumes no responsibility for any errors, omissions, or discrepancies between the information contained herein and the final product delivered.



Equipment features, images, and specifications are subject to change without notice by **GROWER®*

GROWER®

*Designed to
adapt to all your
agricultural needs.*



Equipment features, images, and specifications are subject to change without notice by **GROWER®*



GROWER®

www.growertractor.com