

# **GROWER**®



*Reliable agricultural machinery*

# **Catalog | Range 90-120 HP**

**GT 904 GT 1004 GT 1104 GT 1204**

*\*Equipment features, images, and specifications are subject to change without notice by **GROWER**®*

# GROWER®



## Range 90 - 120 HP

**GT 904 GT 1004 GT 1104 GT 1204**

---



*\*Equipment features, images, and specifications are subject to change without notice by **GROWER®***

## Technical Info

Transmission	GT 904	GT 1004	GT 1104	GT 1204
Drive type	4WD / 4×4			
Gearbox gears number	F12+R12			
Max. forward speed (km/h) / (mph)	32.26 / 20.05		32,26 / 20,11	
Engine				
Engine brand	GROWER			
Engine model	GT-4C6-90C31	GT-4C6-100C35	GT-4C6-110C35	GT-4C6-120C32
Engine type	Inline, 4-stroke, water-cooled, direct injection, turbocharged, intercooled, 4 cylinders			
Engine Rated power (kW) / (hp)	66.2 / 88.78	73.5 / 98.57	81 / 108	88.3 / 118.41
Engine Rated speed (rpm)	2400			
Engine Displacement (L) / (cc)	3.47 / 3470			
Cylinder Bore (mm) / (in)	98 / 3.86	98 / 3.85	98 / 3.86	
Piston Stroke (mm) / (in)	115 / 4.53	115 / 4.52	115 / 4.53	
Fuel tank capacity (L) / (gal)	90 / 23,78		200 / 52,83	
Traction & Force				
Max. traction force (kN / Lbf)	20.727 / 4659.61	23,8875 / 5370,12		28,371 / 6378,05
Max. lifting force (kg / lb)	15.88 / 3569,97	17.64 / 3965.63		21.192 / 4764.15
PTO ( Power Take - Off )				
PTO power (kW / hp)	56.27 / 75.46	62.5 / 83.81		75 / 100.58
PTO type	Rear-mounted, independent			
PTO speed (rpm)	540/760 or 540/1000			
PTO shaft size	8 splines, 6-spline optional			
Hydraulic System				
Number of hydraulic outlets	Two pairs			
Draft control	Height control and float control			
Dimensions & Weights				
Dimensions L xW xH (height to top of safety frame) (mm) / (in)	4530 × 2050 × 2930 / 178 × 80 × 115		4530 × 2050 × 2930 / 178 × 80 × 115	
Wheelbase (mm) / (in)	2080 / 82	2115 / 83		2070 / 82
Front track (mm) / (in)	1285 / 51	1300 / 51	1353 / 53	1288 - 1493 / 51 - 59
Rear track width (mm) / (in)	1350, 1450, 1550 / 53, 57, 61	1300-1600 / 51-62.9		1352-1672/53-66
Min. ground clearance (mm) / (in)	370 / 15	410 / 16.1	400 / 15.75	
Minimum operating weight with cab (kg) / (lb)	2820 / 6217	3250 / 7165		3860 / 8510
Steering & Hitch				
Steering type	Full hydraulic steering on front wheels			
Hitch type / category	Rear-mounted three-point hitch, Category I and II			
Tires				
Front tire specification	8.3-24		9,5-24	
Rear tire specification	14.9-30			
Optional Configuration				
Front ballast (kg) / (lb)	Max. 112 / 246.92 (optional)			
Rear ballast (kg) / (lb)	Max. 200 / 440.92 (optional)			

**GT904** - Cab with A/C, 3 pairs of hydraulic outlets, front & rear iron ballast (1480 kg), optional tires 12.4×24 / 18.4×30

**GT1004 / GT 1104** - Cab with A/C, 3 pairs of hydraulic outlets, front & rear iron ballast (1480 kg), optional tires 12.4×24 / 18.4×34 - 14.9×24 / 23.1×26

**GT 1204** - Cab with A/C, 3 pairs of hydraulic outlets, front & rear iron ballast (1480 kg), optional tires 14.9×24/23.1x26 - 14.9x24/23.1x30

*\*Equipment features and specifications may change without notice from **GROWER**.*

# GROWER®



**Legal Notice:**

The information contained in this catalog, including but not limited to technical specifications, descriptions, configurations, illustrations, images, performance data, capacities, and any other information, is provided for informational and reference purposes only. Such information may be modified, updated, or corrected at any time without prior notice.

**GROWER®** assumes no responsibility for any errors, omissions, or discrepancies between the information contained herein and the final product delivered.



*\*Equipment features, images, and specifications are subject to change without notice by **GROWER®***

# **GROWER**®

*Designed to  
adapt to all your  
agricultural needs.*



*\*Equipment features, images, and specifications are subject to change without notice by **GROWER**®*



**GROWER**®

[www.growertractor.com](http://www.growertractor.com)